

NdBR-80

Ultra High cis Polybutadiene Rubber (NdBR)

Product Introduction

- Kumho NdBR is ultra high cis polybutadiene rubber, produced by 1, 3-butadiene polymerization with a novel neodymium catalyst.
- It is oil extended clear BR
- They have more than 96% of 1,4-cis content.
- Very low glass transition temperature around -100 °C

Product Properties

Property	Typical value	Test Method
	NdBR-40	
ML1+4@100 °C	37	ASTM D 1646
cis content (%)	> 96	FT-IR METHOD
Volatile matter content (%)	Max 0.5	ASTM D 5668
Ash content (%)	Max 0.5	ASTM D 5667

Characteristics and Applications

- Kumho NdBR provides excellent abrasion resistance, low heat build-up and high resilience, which are very much demanded property for tire as well as other applications.
- Typical applications are tires, golf balls, footwears, belts, rubber hoses.

Manufacturer location

- Yeosu plant in Korea

Product safety

- Relevant safety data and references can be found in the safety data sheet.

Shelf life/Conditions

- 2 years from the production date at temperatures not exceeding 35 °C, keeping away from direct sunlight, humidity

Packaging

- Bale weight : 35kg (Wrapped by polyethylene film)
- Box weight : 1,050kg (30 bales)

Head Office (Sales)

East Wing 10-14th Floor, Signature Towers Seoul,
100, Cheonggyecheon-ro, Jung-gu, Seoul, Korea
Tel. +82-2-6961-1114 Fax. +82-2-6961-1459
www.kkpc.com

Research Center (Technical Service)

1557, Yuseongdae-ro, Yuseong-qu, Deajeon, Korea
Tel. +82-42-865-8600 Fax. +82-42-865-5651
pskim@kkpc.com

Yeosu Plant (Quality Assurance)

331, Sandanjungang-ro, Yeosu, Jinnam, Korea
Tel. +82-61-688-7210 Fax. +82-61-688-7219
pskim@kkpc.com