

SAFETY DATA SHEET KUMHO 1763

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010, COMMISSION REGULATION (EU) 2015/830 of 28 May 2015.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name KUMHO 1763

REACH registration number -

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Raw materials for rubber products (tires, rubber shoes, sneakers, rubber hoses, belts)

Uses advised against Not available.

1.3. Details of the supplier of the safety data sheet

Supplier OR of KOREA KUMHO Petrochemical Co., Ltd.

KIST Europe Forschungsgesellschaft mbH

Campus E71

66123 Saarbruecken

Germany

Tel: +49 681 9382 334 Fax: +49 681 9382 319

e-mail: reach.it@kist-europe.de

Manufacturer Korea Kumho Petrochemical Co., Ltd.

64, Sanggae-ro, Nam-gu

Ulsan, Korea 680-180

Tel: +82-52-259-6051~7 Fax: +82-52-259-6053

1.4. Emergency telephone number

Emergency telephone +49 551 19240

GIZ-Nord, Goettingen, Germany (English only)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC/1272/2008)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements

KUMHO 1763

Pictogram



Hazard statements H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains N-(1,3-Dimethylbutyl)-N´-phenyl-1,4-phenylenediamine. May produce an

allergic reaction.

Precautionary statements P273 Avoid release to the environment.

P391 Collect spillage.

P501 Dispose of contents/ container in accordance with national regulations.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Styrene-Butadiene Copolymer

66 - 70 %

CAS number: 9003-55-8

Classification
Not Classified

Distillates (petroleum), hydrotreated heavy naphthenic

26 - 28 %

CAS number: 64742-52-5 EC number: 265-155-0 REACH registration number: 01-

2119467170-45-0008

Classification

Not Classified

Resin acids and Rosin acids, potassium salts

1-5%

CAS number: 61790-50-9 EC number: 263-142-4

Classification
Not Classified

Facid 1-5%

CAS number: 67701-06-8

Classification
Not Classified

KUMHO 1763

N-(1,3-Dimethylbutyl)-N´-phenyl-1,4-phenylenediamine

<1%

CAS number: 793-24-8 EC number: 212-344-0 REACH registration number: 01-

2119485839-15-XXXX

M factor (Acute) = 10 M factor (Chronic) = 10

Classification

Acute Tox. 4 - H302 Skin Sens. 1 - H317 Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410

The full text for all hazard statements is displayed in Section 16.

Composition comments Monomer is registered instead of Styrene-Butadiene-Styrene copolymer. (Registration

number of monomer: 1,3-Butadiene; 01-2119471988-16-****, Styrene; 01-2119457861-32-

****)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information Get medical attention.

Inhalation Move affected person to fresh air and keep warm and at rest in a position comfortable for

breathing. When breathing is difficult, properly trained personnel may assist affected person

by administering oxygen. Get medical attention if any discomfort continues.

Ingestion Rinse mouth. Do not induce vomiting. If vomiting occurs, the head should be kept low so that

vomit does not enter the lungs. Never give anything by mouth to an unconscious person. Get

medical attention if any discomfort continues.

Skin contact Remove contaminated clothing and rinse skin thoroughly with water. Continue to rinse for at

least 15 minutes. Get medical attention if any discomfort continues. Wash contaminated

clothing before reuse.

Eye contact Do not rub eye. Remove any contact lenses and open eyelids wide apart. Continue to rinse

for at least 15 minutes. Continue to rinse for at least 15 minutes.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact May produce an allergic reaction.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treatment may vary with condition of victim and specifics of incident.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Water. Foam. Carbon dioxide (CO2). Dry chemicals.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards Irritating gases or vapours. Dust or gas may ignite by flames. Fire water contaminated with

this chemical must be controlled or prevented from entering environment. Containers can

burst violently or explode when heated, due to excessive pressure build-up.

KUMHO 1763

Hazardous combustion

products

Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting

Keep up-wind to avoid fumes. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out. Fight advanced or massive fires from safe distance or protected location. Avoid inhalation of materials or combustion by-products. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tanks due to fire. Containers close to fire should be removed or cooled with water

Special protective equipment

Use protective equipment appropriate for surrounding materials.

for firefighters

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective clothing as described in Section 8 of this safety data sheet. Avoid heat,

flames and other sources of ignition. Keep upwind. Provide adequate ventilation. Stop leak if possible without any risk. Never use water by itself on spillage; this will spread the spill and cause further contamination.

6.2. Environmental precautions

Environmental precautions

Store away from waterwork or drainage system. Prevent run-off from entering ground, storm sewers and ditches which lead to natural waterways. If large spills, call emergency services to get advice.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Small Spillages: Collect spilled material in appropriate container for disposal. Large Spillages: Avoid lowland and keep upwind. Disposal to licensed waste disposal site in accordance with local waste disposal authority.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Avoid heat, flames and other sources of ignition. Wash thoroughly after handling. Avoid handling which leads to dust formation. Anti-static boots. Anti-static suit. Handle and open container with care.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Store and handle in accordance with all current regulations and standards. Store in tightly-closed, original container in a dry, cool and well-ventilated place. Do not store near heat sources or expose to high temperatures. Earth container and transfer equipment to eliminate sparks from static electricity. Keep away from sources of ignition - No smoking. Keep container tightly sealed when not in use.

7.3. Specific end use(s)

Specific end use(s)

Not available.

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

KUMHO 1763

DNEL Industry - Inhalation; Short term systemic effects: 56.8 mg/m³

DNEL Values correspond to N-(1,3-Dimethylbutyl)-N'-phenyl-1,4-phenylenediamine.

Industry - Inhalation; Long term systemic effects: 7.1 mg/m³ Industry - Dermal; Short term systemic effects: 8 mg/kg/day Industry - Dermal; Long term systemic effects: 1 mg/kg/day

PNEC 2.47 - Fresh water; 0.00037 mg/l

PNEC Values correspond to N-(1,3-Dimethylbutyl)-N'-phenyl-1,4-phenylenediamine.

- Marine water; 0.000037 mg/l

- STP; 0.042 mg/l

8.2. Exposure controls

Protective equipment







Appropriate engineering

controls

Provide adequate general and local exhaust ventilation.

Eye/face protection The following protection should be worn: Chemical splash goggles.

Hand protection Wear suitable gloves.

Other skin and body

protection

Wear suitable protective clothing.

Hygiene measures

Use engineering controls to reduce air contamination to permissible exposure level. Provide

eyewash station and safety shower. Wash hands after handling.

Respiratory protection If ventilation is inadequate, suitable respiratory protection must be worn. Under frequent use

or heavy exposure, respiratory protection may be needed. In case of dust formation, wear

respirator with particle filter.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Solid

Colour Dark brown.

Odour Mild.

Odour threshold Not available. Not available.

pH Not available. Not available.

Melting point Not applicable.

Initial boiling point and range Not applicable.

Flash point 246°C

Evaporation rate Not applicable.

Upper/lower flammability or

explosive limits

Not available.

Other flammability Not available.

Vapour pressure Not applicable.

Vapour density Not applicable.

KUMHO 1763

Relative density Not applicable.

Solubility(ies) Insoluble in water.

Partition coefficient Not applicable.

Auto-ignition temperature > 388°C

Decomposition Temperature Not available.

Viscosity Not applicable.

Explosive properties Not available.

Oxidising properties Not available.

9.2. Other information

Molecular weight ≈ 120,000

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Not available.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended.

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

Will not occur.

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials to avoid Not available.

10.6. Hazardous decomposition products

Hazardous decomposition The

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Oxides of carbon. Hydrocarbons.

products vapours. Oxides of carbon. Hydrocarbons

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Not available.

Acute toxicity - dermal

Notes (dermal LD₅₀) Not available.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Not available.

Skin corrosion/irritation

Animal data Not available.

Serious eye damage/irritation

Serious eye damage/irritation Not available.

Germ cell mutagenicity

KUMHO 1763

Genotoxicity - in vitro

Not available.

Genotoxicity - in vivo

Not available.

Carcinogenicity

Carcinogenicity Not available.

Reproductive toxicity

Reproductive toxicity - fertility Not available.

Reproductive toxicity -

Not available.

development

Specific target organ toxicity - single exposure
STOT - single exposure
Not available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not available.

Skin contact May produce an allergic reaction.

Toxicological information on ingredients.

Distillates (petroleum), hydrotreated heavy naphthenic

Acute toxicity - oral

Acute toxicity oral (LD₅o

5,000.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 5,000.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation 2.18

(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours

mg/l)

Aspiration hazard

Aspiration hazard 380 cps @ 40°C

2.18

Resin acids and Rosin acids, potassium salts

Acute toxicity - oral

Acute toxicity oral (LD₅₀ 2,000.0

mg/kg)

Species Rat

Acute toxicity - dermal

KUMHO 1763

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rat

Acute toxicity - inhalation

Notes (inhalation LC50) Endpoint waived according to REACH Annex VII, IX or XI.

Facid

Acute toxicity - oral

Acute toxicity oral (LD₅o

2,000.0

mg/kg)

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 2,000.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation

0.1621

(LC₅₀ vapours mg/l)

Species Rat

ATE inhalation (vapours

mg/l)

0.1621

N-(1,3-Dimethylbutyl)-N'-phenyl-1,4-phenylenediamine

Acute toxicity - oral

Acute toxicity oral (LD50

mg/kg)

1,005.0

Species Rat

Notes (oral LD50) This test is conducted with male rat.

ATE oral (mg/kg) 1,005.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ 7,940.0

mg/kg)

Species Rabbit

Acute toxicity - inhalation

Notes (inhalation LC50) Endpoint waived according to REACH Annex VII, IX or XI.

Skin corrosion/irritation

Animal data Not irritating.

Serious eye damage/irritation

Serious eye

Slightly irritating.

damage/irritation

KUMHO 1763

Skin sensitisation

Skin sensitisation Guinea pig maximization test (GPMT) - Guinea pig: Sensitising.

Germ cell mutagenicity

Gene mutation:: Negative. Species : Salmonella typhimurium TA 98, TA 100, TA

1535, TA 1537.

Genotoxicity - in vivo Chromosome aberration: Negative. Species : rat.

Carcinogenicity

Carcinogenicity NOAEL 1000 ppm, Oral, Rat

Reproductive toxicity

Reproductive toxicity -

fertility

Screening: - NOAEL 100 mg/kg/day, Oral, Rat P

Reproductive toxicity -

development

Maternal toxicity: - NOAEL: 50 mg/kg/day, Inhalation, Rat

SECTION 12: Ecological Information

Ecotoxicity There are no data on the ecotoxicity of this product.

12.1. Toxicity

Acute toxicity - fish Not available.

Acute toxicity - aquatic

invertebrates

Not available.

Acute toxicity - aquatic plants Not available.

Acute toxicity - Not available.

microorganisms

Acute toxicity - terrestrial Not available.

Chronic toxicity - fish early life Not available.

stage

Short term toxicity - embryo

and sac fry stages

Not available.

Chronic toxicity - aquatic

Not available.

invertebrates

Ecological information on ingredients.

Distillates (petroleum), hydrotreated heavy naphthenic

Acute toxicity - fish , 96 hours: > = 100 mg/l, Pimephales promelas (Fat-head Minnow)

Endpoint: NOEL.

Acute toxicity - aquatic

invertebrates

, 48 hours: > = 10000 mg/l, Daphnia magna

Endpoint: NOEL.

Acute toxicity - aquatic

plants

, 72 hours: > = 100 mg/l, Selenastrum capricornutum

Endpoint: NOEL.

(based on the growth rate)

KUMHO 1763

Acute toxicity -, >: > 1.93 mg/l, Activated sludge

microorganisms Endpoint: NOEL.

Exposure time: 10 min.

Chronic toxicity - aquatic

invertebrates

, 21 days: 10 mg/l, Daphnia magna

Endpoint: NOEL.

Resin acids and Rosin acids, potassium salts

Acute toxicity - fish LC50, 96 hours: 60.3 mg/l, Brachydanio rerio (Zebra Fish)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 3.8 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

NOEC, 96 hours: 0.0125 mg/l, Scenedesmus subspicatus

Facid

Acute toxicity - fish LC50, 96 hours: 1354.4 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic

invertebrates

EC₅o, 48 hours: > 4.8 mg/l, Daphnia magna

Acute toxicity - aquatic

plants

EC₅₀, 72 hours: > 0.9 mg/l, Selenastrum capricornutum

(based on the growth rate)

N-(1,3-Dimethylbutyl)-N´-phenyl-1,4-phenylenediamine

Acute aquatic toxicity

LE(C)50 $0.01 < L(E)C50 \le 0.1$

M factor (Acute) 10

Acute toxicity - fish LC50, 96 hours: 0.028 mg/l, Oryzias latipes (Red killifish)

Acute toxicity - aquatic

invertebrates

EC₅₀, 48 hours: 0.69 mg/l, Daphnia magna

Acute toxicity - aquatic

NOEC, 72 hours: 0.23 mg/l,

plants

Species: Desmodesmus subspicatus.

Acute toxicity -

microorganisms

EC₅₀, 3 hours: 420 mg/l, Activated sludge

Chronic aquatic toxicity

NOEC $0.001 < NOEC \le 0.01$

Degradability Non-rapidly degradable

M factor (Chronic) 10

life stage

Chronic toxicity - fish early LOEC, : 0.011 mg/l, Oryzias latipes (Red killifish)

NOEC, : 0.0037 mg/l, Oryzias latipes (Red killifish)

Exposure duration: 30 days.

Chronic toxicity - aquatic

invertebrates

NOEC, 21 days: 0.028 mg/l, Daphnia magna LOEC, 21 days: 0.087 mg/l, Daphnia magna

KUMHO 1763

Toxicity to soil Endpoint waived according to REACH Annex VII, IX or XI.

12.2. Persistence and degradability

Persistence and degradability Not available.

Biodegradation Not available.

Ecological information on ingredients.

N-(1,3-Dimethylbutyl)-N´-phenyl-1,4-phenylenediamine

Phototransformation Water - DT₅₀ : 1.7 hours

Stability (hydrolysis) pH7 - Half-life : 5 hours 50°C @ °C

Biodegradation Water - Degradation (%) 2: 28 days

Water - Degradation (%) 97: 22 hours

12.3. Bioaccumulative potential

Partition coefficient Not applicable.

Ecological information on ingredients.

N-(1,3-Dimethylbutyl)-N´-phenyl-1,4-phenylenediamine

Bioaccumulative potential BCF: 1.2 ~ 23, Cyprinus carpio (Common carp)

12.4. Mobility in soil

Mobility Not available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information

Dispose of contents/containers in accordance with local/regional/national/international

regulations. Waste is suitable for incineration. If the waste contains designated waste and difficult to separate, incinerate it or reduce the volume following the similar way as

incineration. If applicable, pretreat waste with oil/water separation.

Disposal methods Confirm disposal procedures with environmental engineer and local regulations. Dispose of

the waste by oneself or contact disposal company.

SECTION 14: Transport information

14.1. UN number

UN No. (ADR/RID) 3077
UN No. (IMDG) 3077
UN No. (ICAO) 3077

14.2. UN proper shipping name

KUMHO 1763

Proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-(1,3-

(ADR/RID) DIMETHYLBUTYL)-N'- PHEN-YL-P-PHENYLENEDIAMINE)

Proper shipping name (IMDG) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-(1,3-

DIMETHYLBUTYL)-N'- PHEN-YL-P-PHENYLENEDIAMINE)

Proper shipping name (ICAO) ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (N-(1,3-

DIMETHYLBUTYL)-N'- PHEN-YL-P-PHENYLENEDIAMINE)

14.3. Transport hazard class(es)

ADR/RID class 9

IMDG class 9

ICAO class/division 9

14.4. Packing group

ADR/RID packing group III

IMDG packing group

ICAO packing group

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



14.6. Special precautions for user

EmS F-A. S-F

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Authorisations (Title VII

Regulation 1907/2006)

No specific authorisations are known for this product.

Restrictions (Title VIII

No specific restrictions on use are known for this product.

Regulation 1907/2006)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out for Resin acids and Rosin acids, potassium salts (CAS:61790-50-9), Facid (CAS:67701-06-8), Distillates (petroleum), hydrotreated heavy naphthenic (CAS:64742-52-5) and N-(1,3-Dimethylbutyl)-N'-phenyl-1,4-phenylenediamine (CAS:793-24-8).

SECTION 16: Other information

Abbreviations and acronyms

Precautionary Statements In Full.

used in the safety data sheet

P501 Dispose of contents/container in accordance with local/regional/national/international

regulation.

Issued by KIST Europe

KUMHO 1763

Revision date 16/04/2018

Revision 2

SDS status Approved.

Hazard statements in full H302 Harmful if swallowed.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

EUH208 Contains N-(1,3-Dimethylbutyl)-N´-phenyl-1,4-phenylenediamine. May produce an

allergic reaction.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.